


NOTE:

1. WHERE INFILTRATION TRENCH BEGINS ADJACENT TO PAVING, THE SLOPE AND OFFSETS SHALL BE PER DETAIL.
2. TREATMENT SOIL: REFER TO APPENDIX L OF THE ALAMEDA COUNTYWIDE CLEAN WATER PROGRAM, C.3 STORMWATER TECHNICAL GUIDANCE MANUAL FOR IMPORTED MATERIAL SPECIFICATION.
3. IN SITUATIONS WITH HIGH WATER TABLE, TRENCH SHALL BE LINED ON SIDES AND BOTTOM WITH A WOVEN GEOTEXTILE FABRIC, MIRAFI 500 X, OR EQUAL, TO PREVENT INFILTRATION. 12" DEPTH SHALL BECOME 3".
4. NO WOOD BARK SHALL BE PLACED IN TREATMENT AREA. ROCK OF INERT MULCH OK AS APPROVED.



SCALE: 1" = 1'-0"

CITY OF FREMONT PARK STANDARD DETAILS

TREATMENT AREA

DATE APPROVED BY CITY COUNCIL
December 13, 2011

RESOLUTION NO. 2011-65

SENIOR LANDSCAPE ARCHITECT

COMMUNITY SERVICES DIRECTOR

APR. REVISED DATE

REVISIONS

FILE NO.	SCALE	DRAWN	CHECKED	DATE	DWG NO.	
PSD SW-1.DWG	1" = 1'-0"	MAM	RER	05/10/2011	PSD SW-1	1 OF 1